



PRODUCT DESCRIPTION


DESCRIPTION	LED DOWNLIGHT ENGINE
CATEGORY	IP20 - FOR INDOOR USE ONLY
MATERIAL	MACHINED ALUMINIUM
FINISH	BLACK ANODISED
DIMMING	1-10V DALI PHASE SWITCHED
POWER SUPPLY	REMOTE DRIVER
ACCESSORIES	SEE BELOW
WEIGHT	0.2kg

LIGHT ENGINE


POWER	12.8W
CURRENT	700mA CONSTANT CURRENT
LAMP LUMENS	2700K 1030lm 3000K 1110lm 4000K 1205lm
COLOUR RENDERING	CRI 98 Typ.
BEAM DISTRIBUTION	FWHM 10° + Accessories
LAMP LIFE	>105,000 hours - LM70




DIMENSIONS




ACCESSORIES



BEAM WIDTH LENSES
5031-0106 - 17° NARROW
5031-0037 - 25° NARROW FLOOD
5031-0038 - 36° FLOOD
5031-0039 - 60° WIDE FLOOD



BEAM SHAPING LENSES
5031-0096 - 10X25° LINEAR
5031-0108 - 10X36° LINEAR
5031-0110 - 10X60° LINEAR
5031-0115 - 36X36° SQUARE



BEAM CONTROL LENSES
5031-0116 - AIMABLE (PAIR)
5031-0002 - H/C LOUVRE



COLOUR LENSES
5031-0053 - ¼ CTO
5031-0054 - ½ CTO
5031-0157 - CLEAR*

* To be used with colour gels.

PRODUCT CODE E1100A.XX

LUMINAIRE TYPE	COLOUR TEMP	DIMMING	ACCESSORIES **
E1100A. LED MODULE	27. 2700K 30. 3000K 40. 4000K	+ 1-10V + DALI + PHASE	+ BEAM WIDTH LENSES + BEAM SHAPING LENSES + BEAM CONTROL LENSES + COLOUR LENSES

** Up to 3 accessories can be attached.