



PRODUCT DESCRIPTION


DESCRIPTION	LED DOWNLIGHT ENGINE
CATEGORY	IP20 - FOR INDOOR USE ONLY
MATERIAL	MACHINED ALUMINIUM
FINISH	BLACK ANODISED
DIMMING	1-10V DALI PHASE SWITCHED
POWER SUPPLY	REMOTE DRIVER
ACCESSORIES	SEE BELOW
WEIGHT	0.36kg

LIGHT ENGINE


POWER	17.6 W
CURRENT	500mA CONSTANT CURRENT
LAMP LUMENS	2700K 1670lm 3000K 1780lm 4000K 1950lm
COLOUR RENDERING	CRI 98 Typ.
BEAM DISTRIBUTION	FWHM 10° + Accessories
LAMP LIFE	>105,000 hours - LM70




DIMENSIONS



ACCESSORIES



BEAM WIDTH LENSES
5031-0106 - 17° NARROW
5031-0037 - 25° NARROW FLOOD
5031-0038 - 36° FLOOD
5031-0039 - 60° WIDE FLOOD



BEAM SHAPING LENSES
5031-0096 - 10X25° LINEAR
5031-0108 - 10X36° LINEAR
5031-0110 - 10X60° LINEAR
5031-0115 - 36X36° SQUARE



BEAM CONTROL LENSES
5031-0116 - AIMABLE (PAIR)
5031-0002 - H/C LOUVRE



COLOUR LENSES
5031-0053 - ¼ CTO
5031-0054 - ½ CTO
5031-0157 - CLEAR*

* To be used with colour gels.

PRODUCT CODE E1600A.XX

LUMINAIRE TYPE	COLOUR TEMP	DIMMING	ACCESSORIES **
E1600A. LED MODULE	27. 2700K 30. 3000K 40. 4000K	+ 1-10V + DALI + PHASE	+ BEAM WIDTH LENSES + BEAM SHAPING LENSES + BEAM CONTROL LENSES + COLOUR LENSES

** Up to 3 accessories can be attached.